

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

AMENDMENTS TO THE CLAIMS

1. (currently amended) A SONET multiplexed communications system, comprising:

at least one SONET input signal path configured to receive at least one input signal, the SONET input signal path including a pointer interpreter configured to interpret at least one input signal pointer;

at least one SONET output signal path configured to transmit at least one output signal corresponding to the input signal, the SONET output signal path including a pointer generator configured to generate at least one output signal pointer; and

a time slot interchange circuit operatively coupled between the pointer interpreter and the pointer generator included in the SONET input and output signal paths, respectively, and the time slot interchange circuit being configured to provide time division multiplexed connections for the input and output signals,

wherein the SONET input signal path ~~includes a pointer interpreter configured to interpret at least one input signal pointer serially coupled to~~ further includes a synchronization buffer serially coupled to the pointer interpreter, the synchronization buffer being configured to transfer the input signal from a respective clock rate of the SONET input signal path

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

to a respective clock rate of the time slot interchange circuit,
and

wherein the SONET output signal path ~~includes a pointer generator configured to generate at least one output signal~~ pointer serially coupled to further includes a first-in first-out buffer serially coupled to the pointer generator, the first-in first-out buffer being configured to transfer the output signal from the respective clock rate of the time slot interchange circuit to a respective clock rate of the SONET output signal path.

2. (original) The system of claim 1 wherein the pointer interpreter precedes the synchronization buffer in the SONET input signal path.

3. (original) The system of claim 1 wherein the synchronization buffer precedes the pointer interpreter in the SONET input signal path.

4. (original) The system of claim 1 wherein the input signal is an STS-M ($M > 1$) signal, and the SONET input signal path further includes an alignment buffer operatively coupled between the

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

synchronization buffer and the time slot interchange circuit and configured to perform column alignment on the STS-M signal.

5. (previously presented) A SONET multiplexed communications system, comprising:

at least one SONET input signal path configured to receive at least one input signal;

at least one SONET output signal path configured to transmit at least one output signal corresponding to the input signal; and

a time slot interchange circuit operatively coupled between the SONET input and output signal paths and configured to provide time division multiplexed connections for the input and output signals,

wherein the SONET input signal path includes a pointer interpreter configured to interpret at least one input signal pointer serially coupled to a synchronization buffer configured to transfer the input signal from a respective clock rate of the SONET input signal path to a respective clock rate of the time slot interchange circuit, and

wherein the SONET output signal path includes a pointer generator configured to generate at least one output signal pointer serially coupled to a first-in first-out buffer configured

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

to transfer the output signal from the respective clock rate of the time slot interchange circuit to a respective clock rate of the SONET output signal path,

wherein the input signal is an STS-M ($M > 1$) signal, and the SONET input signal path further includes an alignment buffer operatively coupled between the synchronization buffer and the time slot interchange circuit and configured to perform column alignment on the STS-M signal, and

wherein the alignment buffer includes a multitap delay element and a controller circuit, the multitap delay element having an input and a plurality of outputs and being configured to receive the STS-M signal at the input and provide increasingly delayed versions of the STS-M signal at successive ones of the outputs, the controller circuit being configured to select a delayed version of the STS-M signal from one of the outputs for application to the time slot interchange circuit.

6. (original) The system of claim 1 wherein the at least one SONET input signal path comprises a plurality of SONET input signal paths and the at least one SONET output signal path comprises a plurality of SONET output signal paths, the number of

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

SONET input signal paths being greater than the number of SONET output signal paths.

7. (currently amended) A SONET multiplexed communications system, comprising:

at least one SONET input signal path configured to receive at least one input signal, the SONET input signal path including a synchronization buffer;

at least one SONET output signal path configured to transmit at least one output signal corresponding to the input signal, the SONET output signal path including a pointer interpreter configured to interpret at least one input signal pointer, a pointer generator configured to generate at least one output signal pointer, and a first-in first-out buffer serially coupled between the pointer interpreter and the pointer generator; and

at least one time slot interchange circuit operatively coupled between the synchronization buffer and the pointer interpreter included in the SONET input and output signal paths, respectively, and the time slot interchange circuit being configured to provide time division multiplexed connections for the input and output signals,

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

wherein the ~~SONET input signal path includes a~~
synchronization buffer included in the SONET input signal path is
configured to transfer the input signal from a respective clock
rate of the SONET input signal path to a respective clock rate of
the time slot interchange circuit, and

wherein the ~~SONET output signal path includes a pointer~~
~~interpreter configured to interpret at least one input signal~~
~~pointer, a pointer generator configured to generate at least one~~
~~output signal pointer, and a first-in first-out buffer included in~~
the SONET output signal path is serially coupled between the
~~pointer interpreter and the pointer generator and configured to~~
transfer the output signal from the respective clock rate of the
time slot interchange circuit to a respective clock rate of the
SONET output signal path.

8. (original) The system of claim 7 wherein the input signal is
an STS-M ($M > 1$) signal, and the SONET input signal path further
includes an alignment buffer operatively coupled between the
synchronization buffer and the time slot interchange circuit and
configured to perform column alignment on the STS-M signal.

Application No. 09/836,777

Filed: April 17, 2001

TC Art Unit: 2664

Confirmation No.: 6860

9. (previously presented) A SONET multiplexed communications system, comprising:

at least one SONET input signal path configured to receive at least one input signal;

at least one SONET output signal path configured to transmit at least one output signal corresponding to the input signal; and

at least one time slot interchange circuit operatively coupled between the SONET input and output signal paths and configured to provide time division multiplexed connections for the input and output signals,

wherein the SONET input signal path includes a synchronization buffer configured to transfer the input signal from a respective clock rate of the SONET input signal path to a respective clock rate of the time slot interchange circuit, and

wherein the SONET output signal path includes a pointer interpreter configured to interpret at least one input signal pointer, a pointer generator configured to generate at least one output signal pointer, and a first-in first-out buffer serially coupled between the pointer interpreter and the pointer generator and configured to transfer the output signal from the respective clock rate of the time slot interchange circuit to a respective clock rate of the SONET output signal path,

-8-

WEINGARTEN, SCHURGIN,
GAGNERIN & LEBOVICI LLP
TEL. (517) 542-2290
FAX. (517) 451-0313

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

wherein the input signal is an STS-M ($M > 1$) signal, and the SONET input signal path further includes an alignment buffer operatively coupled between the synchronization buffer and the time slot interchange circuit and configured to perform column alignment on the STS-M signal, and

wherein the alignment buffer includes a multitap delay element and a controller circuit, the multitap delay element having an input and a plurality of outputs and being configured to receive the STS-M signal at the input and provide increasingly delayed versions of the STS-M signal at successive ones of the outputs, the controller circuit being configured to select a delayed version of the STS-M signal from one of the outputs for application to the time slot interchange circuit.

10. (original) The system of claim 7 wherein the at least one SONET input signal path comprises a plurality of SONET input signal paths and the at least one SONET output signal path comprises a plurality of SONET output signal paths, the number of SONET input signal paths being greater than the number of SONET output signal paths.

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

11. (currently amended) A method of operating a SONET multiplexed communications system, comprising the steps of:

providing at least one SONET input signal path including a pointer interpreter and a synchronization buffer serially coupled to the pointer interpreter;

providing at least one SONET output signal path including a pointer generator and a first-in first-out buffer serially coupled to the pointer generator;

providing a time slot interchange circuit operatively coupled between the pointer interpreter and the pointer generator included in the SONET input and output signal paths, respectively;

receiving at least one input signal by ~~at least one~~ the SONET input signal path;

interpreting at least one input signal pointer by ~~a~~ the pointer interpreter included in the SONET input signal path;

transferring the input signal from a respective clock rate of the SONET input signal path to a respective clock rate of ~~a~~ the time slot interchange circuit by ~~a~~ the synchronization buffer included in the SONET input signal path;

providing time division multiplexed connections for the input signal and at least one corresponding output signal by the time slot interchange circuit;

-10-

WEINGARTEN, SCHURGIN,
CAGNERIS & LEBOVICI LLP
TEL. (617) 542-2250
FAX. (617) 451-0313

Application No. 09/836,777
Filed: April 17, 2001
TC Art Unit: 2664
Confirmation No.: 6860

generating at least one output signal pointer by ~~a~~ the
pointer generator included in ~~at least one~~ the SONET output signal
path;

transferring the corresponding output signal from the
respective clock rate of the time slot interchange circuit to a
respective clock rate of the SONET output signal path by ~~a~~ the
first-in first-out buffer included in the SONET output signal
path; and

transmitting the corresponding output signal by the SONET
output signal path.

12. (original) The method of claim 11 further including the step
of performing column alignment on the input signal by an alignment
buffer included in the SONET input signal path.

-11-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEROVICK LLP
TEL. (617) 542-2290
FAX. (617) 451-0913